

Safety EN

Full lift safety valve with spring loading. (AIT)



EP

AP

ES

CP

EP






AP






ES

CP

Mod. 496

Mod. 495

Connection: Flange x Flange
 DN1 x DN2: 20x32 to 200x300
 Material:  Cast Iron. PN-16
 Nodular iron. PN-40. 350°C
 Cast steel. PN-40
 Stainless steel. PN-40
 Seal:  Metal

Connection: Female thread x Female thread
 FR1 x FR2: 3/4"x1 1/4" and 1"x1 1/2"
 Material:  Cast Iron. PN-16
 Nodular iron. PN-40. 350°C
 Cast steel. PN-40
 Stainless steel. PN-40
 Seal:  Metal

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.
 Design in accordance with "International Standard ISO 4126-1 Safety Valves".

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.
 Design in accordance with "International Standard ISO 4126-1 Safety Valves".

Depending on version



-60°C to +450°C



0,20 bar to 40,00 bar



Steam/Gases/Liquids

Depending on version



-60°C to +450°C



0,20 bar to 40,00 bar



Steam/Gases/Liquids